

IMAGE PROCESSING METHOD, IMAGE PROCESSING APPARATUS,
AND PROGRAMS THEREOF

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to creation of a table used for separating color into color of coloring agent available in an image formation apparatus.

Related Background Art

10 Conventionally, processing for separating the color into data of the coloring agent available in a color printer (hereinafter, called ink color separation processing) is constituted as shown in Fig. 22. Hereinafter, an explanation of the ink color separation
15 processing will be given with reference to Fig. 22.

Numeral 2201 denotes a luminance/density conversion unit, numeral 2202 denotes a UCR/BG processing unit, numeral 2203 denotes a BG quantity setting unit and numeral 2204 denotes a UCR (under-
20 color removal) quantity setting unit. In the luminance/density conversion unit 2201, luminance information of 8-bit data of R', G' and B' being input are respectively converted into C, M and Y data based on following expressions.

25 $C = -a \log(R'/255) \dots (1)$
 $M = -a \log(G'/255) \dots (2)$
 $Y = -a \log(B'/255) \dots (3)$

20250720

where, α denotes an arbitrary real number.

Next, the C, M and Y data are respectively converted by use of $\beta(\text{Min}(C, M, Y), \mu)$ set in a BG coefficient setting unit 1603 and a value $\mu\%$ set in a UCR coefficient setting unit 1604 as follows.

$$C' = C - (\mu/100) \times \text{Min}(C, M, Y) \quad \dots (4)$$

$$M' = M - (\mu/100) \times \text{Min}(C, M, Y) \quad \dots (5)$$

$$Y' = Y - (\mu/100) \times \text{Min}(C, M, Y) \quad \dots (6)$$

$$K' = \beta(\text{Min}(C, M, Y), \mu) \times (\mu/100) \times \text{Min}(C, M, Y) \quad \dots (7)$$

where, the $\beta(\text{Min}(C, M, Y), \mu)$ denotes a real number which is varied by the $\text{Min}(C, M, Y)$ and the value μ . A dyeing method of K ink can be set according to a value of this real number.

Since the UCR quantity and the BG quantity give great influence to a color reproduction region of the color printer and graininess appeared in printing performed by the printer accompanied by the dyeing method of K ink, those quantities become important parameters for the color printer.

However, conventionally, since the UCR quantity is calculated by multiplying an UCR coefficient μ by the $\text{Min}(C, M, Y)$, and the BG quantity is calculated by multiplying the BG coefficient β by the UCR coefficient μ by the $\text{Min}(C, M, Y)$, it was impossible to set optimized UCR quantity and BG quantity every hue, whereby the following problems existed.

FILE NO. 0720060

In a certain hue of a target printer, in spite of a fact that color of higher chroma can be outputted, the ink color separation processing which can reproduce such the color can not be provided.

5 In spite of a fact that influence of graininess caused by the K ink can be more reduced according to combination of ink quantity, the corresponded ink color separation processing can not be provided.

10 In the above conventional example, non-linear characteristic in case of the mixture of plural inks can not be sufficiently absorbed, and distorted characteristic is remained in lightness, hue and chroma.

15 SUMMARY OF THE INVENTION

An object of the present invention is to solve the above problems.

20 An object of the first invention is to effectively use a color reproduction region of an image formation apparatus and avoid to have distorted characteristic in lightness, hue and chroma.

An object of the second invention is to reduce the influence of graininess caused by K ink.

25 The first invention relates to an image processing method, which creates a table for separating color into color of coloring agent available in an image formation apparatus, is characterized in that a maximum line in

THE PATENT OFFICE

the color reproduction region of the image formation apparatus is defined, internal lines in the color reproduction region of the image formation apparatus are defined, and interpolation processing is executed
5 on the basis of the maximum line and the internal lines, whereby the table is created.

The second invention relates to an image processing method, which creates a table for separating color into color of coloring agent available in an
10 image formation apparatus, is characterized in that a first line from black to white is defined, plural second lines from white to primary color and secondary color are defined, plural third lines from the primary color and the secondary color to black are defined, and
15 the table is created according to the first line, the second lines and the third lines.

Other objects and features of the present invention will become apparent from the following detailed description and the attached drawings.

20

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram indicating the structure of a first embodiment;

Figs. 2A, 2B and 2C are views for respectively
25 explaining a table of an ink color separation table unit 105 shown in Fig. 1, a dividing method of dividing an input cube into six tetrahedrons and K ink dyeing

THE END

points;

Fig. 3 is a flow chart indicating the basic structure of an ink color separation table creation unit 104 shown in Fig. 1;

5 Figs. 4A, 4B, 4C, 4D, 4E and 4F are views for explaining the divided six tetrahedrons;

Fig. 5 is a flow chart for detailedly explaining internal interpolation processing executed in a step S3-4 shown in Fig. 3;

10 Fig. 6 is a view indicating ink contour lines of an internal interpolation result in a case where changing curves of ink quantity on three sides of a triangle are exemplified;

15 Fig. 7 is a flow chart for explaining two-dimensional interpolation processing executed for a target triangle in a step S5-3 shown in Fig. 5;

20 Fig. 8 is a flow chart for explaining processing executed in a step S7-4, where the ink contour line is created by connecting ink quantity same-level points on total six lines consisted of three sides of the target triangle and three lines of three maximum value points;

25 Fig. 9 is a view for explaining creation of the contour line of the target triangle in a case where ink quantity maximum values on three sides are identical each other;

Fig. 10 is a view for explaining creation of the contour line of the target triangle in a case where the

TOP SECRET

maximum values on two sides are identical each other and the maximum value on one side is equal to zero;

Fig. 11 is a view for explaining creation of the contour line of the target triangle in a case where the maximum values on two sides are identical each other and points of the maximum values exist on one vertex;

Fig. 12 is a view for explaining an example of interpolation processing executed inside a triangle formed by connecting vertexes W-C-Bk shown in Fig. 2, and indicating examples of the C, M, Y and K ink quantity curves on each side;

Figs. 13A, 13B, 13C and 13D are views showing the contour lines of each ink in the target triangle shown in Fig. 12;

Fig. 14 is a view showing the structure of a system according to the present embodiment;

Fig. 15 is a flow chart for explaining two-dimensional interpolation processing executed in a second embodiment;

Fig. 16 is a view indicating ink contour lines according to an internal interpolation processing result in the second embodiment;

Fig. 17 is a view for explaining the concrete contents of a non-linear approximation step;

Fig. 18 is a view for explaining an approximation curve when a value of an approximation parameter a is varied in a step S9-1, where the approximation

FIG. 18 = 6720000

parameter a is set;

Fig. 19 is a view for explaining creation of the contour line of the target triangle in a case where the maximum values on two sides are identical each other and points of the maximum values exist on one vertex;

Figs. 20A, 20B, 20C and 20D are views for explaining the contour lines of each ink in the target triangle;

Fig. 21 is a view for explaining a method of dividing an input cube into eight tetrahedrons in a case where color ink of red or green other than C, M, Y and K is used; and

Fig. 22 is a view for explaining processing for separating color data into color of coloring agent available in a conventional color printer.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS
(First Embodiment)

Fig. 1 is a view showing an outline of image processing according to the present embodiment.

Numeral 101 denotes a color matching processing unit for matching reproduction characteristic of R, G and B data with color available in a printer. Numeral 102 denotes an ink color separation processing unit for respectively converting R', G' and B' multi-level data from the color matching processing unit 101 into color of coloring agent C' (cyan), M' (magenta), Y' (yellow)

FIG. 20 OF 20000

Patch data of C', M', Y' and K' held in the computer 1401 shown in Fig. 14 are respectively transmitted to the printer 1403 through a cable, a network (not shown) or the like in order to print the patch data by the printer 1403. In the printer 1403, the data of C', M', Y' and K' are directly transmitted to the halftone processing unit 103 respectively while bypassing the color matching processing unit 101 and the ink color separation processing unit 102 shown in Fig. 1. In the halftone processing unit 103, only halftone processing is executed to the data of C', M', Y' and K' to perform the print. The printed patch sample 1405 is measured in the colorimeter 1404 shown in Fig. 14 to be taken into the computer 1401. As the patch sample 1405, it may be the one, by which ink characteristic of the printer can be checked, such as gradation patterns of primary colors C, M, Y and K, secondary colors CM, MY, YC, CK, MK and YK, tertiary colors CMY, CMK, MYK and YCK, quartic colors CMYK or the like available in the printer. In an example shown in Fig. 14, as a printer characteristic input unit 106 shown in Fig. 1, the colorimeter 1404 is used, and as the ink color separation table creation unit 104, the computer 1401 is used. Therefore, actual processing in the ink color separation table creation unit 104 explained in detail with reference to Fig. 2 and the following drawings is executed using the computer 1401,

TOP SECRET

and ink color separation tables are created. The
created ink color separation tables are downloaded to
the ink color separation table unit 105 in the printer
1403 through a cable or a network (not shown) in order
5 to perform the print from the computer 1401.

Next, processing of color image data using
downloaded data of the ink color separation tables will
be explained. Color matching processing is executed to
multi-level color image data of R, G and B in the color
10 matching processing unit 101 shown in Fig. 1 so as to
match with color reproduction characteristic of the
monitor 1402 being used by a user. The matching
processed color image data of R', G' and B' are
respectively separated into data of ink colors in the
15 ink color separation processing unit 102 according to
the interpolation processing on the basis of data of
the previously created ink color separation table unit
105. The multi-level data of C', M', Y' and K'
separated into the data of ink colors are respectively
20 converted into data of which gradation number can be
reproduced by the printer in the halftone processing
unit 103, then the print is performed in the printer
1403.

Hereinafter, generation method of data downloaded
25 to the ink color separation table unit 105 will be
explained in detail with reference to Figs. 2A to 2C
and the following drawings.

FOR REFERENCE

Fig. 2A is a view for explaining the ink color separation table unit 105. As shown in Fig. 2A, data corresponding to grid points distributed in grid-like on a cube on a RGB three dimensional space is stored as a table corresponding to the input color image data of R', G' and B'. In the ink color separation processing unit 102, in case of not existing the input color image data of R', G' and B' on the grid points of the ink color separation table unit 105, the interpolation processing is executed using data of adjacent grid points. As interpolation method, although there are plural methods such as a tetrahedron interpolation, a cubic interpolation and the like, any interpolation method may be used because ink separation table creation method and image processing of the present embodiment are not depended on a specific interpolation method.

Fig. 2B is a view for explaining concrete table creation methods related to Fig. 3 and the following drawings. Eight vertexes on the cube shown in Fig. 2A are assumed as W, C, M, Y, R, G, B and Bk, and lines obtained by connecting the above vertexes such as W-C, W-M, W-Y, W-R, W-G and B-Bk are indicated by actual lines or dot lines. When it is assumed that bit number of input data of the ink color separation processing unit 102 is eight, coordinates of each of the vertexes W, C, M, Y, R, G, B and Bk are expressed as follows.

TOP SECRET

That is, $W = (255, 255, 255)$, which indicates White, i.e., color of printing papers. $C = (0, 255, 255)$, which indicates cyan original color. $M = (255, 0, 255)$, which indicates magenta original color. $Y =$
5 $(255, 255, 0)$, which indicates yellow original color. $R = (255, 0, 0)$, which indicates red original color. $G = (0, 255, 0)$, which indicates green original color. $B = (0, 0, 255)$, which indicates blue original color. $Bk = (0, 0, 0)$, which indicates black, i.e., the most dark
10 point expressed in the printer.

The ink color separation table creation method according to the present embodiment creates ink color separation tables related to the lines obtained by connecting the above vertexes such as W-C, W-M, W-Y, W-
15 R, W-G, B-Bk and W-Bk. Then, with respect to ink colors corresponding to internal grid points, data of all the tables is created by internal interpolation processing.

Fig. 2C is a view for explaining ink (K ink)
20 dyeing points and explaining a fact that the ink dyeing points can be three-dimensionally and sequentially controlled by seven dots on the seven lines W-Bk, W-C, W-M, W-Y, W-R, W-G and B-Bk.

Fig. 3 is a flow chart for explaining functions of
25 the ink color separation table creation unit 104.

A step S3-0, which is a start step, starts to create tables to be downloaded to the ink color

TOP SECRET

Black, Red-Black, Green-Black and Blue-Black.

A step S3-6, which is a step of executing the internal interpolation processing, creates the ink color separation tables corresponding to each of grid points inside a space defined by the lines formed in the steps S3-1 to S3-5.

Tables, in which influence of graininess caused by black ink can be possibly suppressed while maximizing a color reproduction region in the printer, can be set by creating tables of setting optimum UCR (under-color removal) quantity or BG quantity every hue in processing of the table creation executed in the step S3-5.

The contents of the internal interpolation processing executed in the step S3-6 will be explained with reference to Figs. 4A to 4F and the following drawings. In the internal interpolation processing executed in the step S3-6, there obtained six divided tetrahedrons of which each of planes is formed by a triangle as shown in Figs. 4A to 4F, and the interpolation processing is executed every tetrahedron. Fig. 4A indicates a tetrahedron structured by vertexes W, R, M and Bk. Fig. 4B indicates a tetrahedron structured by vertexes W, M, B and Bk. Fig. 4C indicates a tetrahedron structured by vertexes W, C, B and Bk. Fig. 4D indicates a tetrahedron structured by vertexes W, Y, R and Bk. Fig. 4E indicates a

TOP SECRET

tetrahedron structured by vertexes W, Y, G and Bk.
Fig. 4F indicates a tetrahedron structured by vertexes
W, C, G, and Bk.

Fig. 5 is a flow chart for explaining concrete
5 processing of the internal interpolation processing
executed in the step S3-6.

A step S5-1, which is a ink color selection step,
sequentially selects ink colors of cyan, magenta,
yellow and black so as to determine ink quantity
10 corresponding to each of grids in the following steps.
A step S5-2, which is a step of selecting the
tetrahedron and dividing (separating) it into plural
triangles, sequentially selects the six tetrahedrons
shown in Figs. 4A to 4F, and separates those
15 tetrahedrons into plural triangles. As separating
method of separating the tetrahedron into plural
triangles, e.g., in a case shown in Fig. 4A, at first,
the tetrahedron is separated into four triangles of a
triangle WMR, a triangle WMBk, a triangle WRBk and a
20 triangle MRBk which structure the tetrahedron. Then,
internal of the tetrahedron WMRBk is separated into
plural triangles by planes parallel to a triangle WRM
corresponding to the number of grids.

A step S5-3 is a step of executing two-dimensional
25 interpolation processing to target triangles. The
contents of the two-dimensional interpolation
processing executed to each of the triangles will be

TOP SECRET

explained in detail with reference to Fig. 6 and the following drawings.

5 A step S5-4, which is a calculation step of calculating distance between an ink contour line of interpolation result and each grid, calculates distance between each of contour lines shown in Fig. 6 created according to the step S5-3 of executing the two-dimensional interpolation processing and each of grids corresponding to tables in the ink color separation table unit 105 for each of the triangles. A step S5-5, which is a step of determining ink quantity of a target grid, determines the shortest distance calculated according to a result obtained in the step S5-4 which calculates the distance between the ink contour line of the interpolation result and the each grid as the ink quantity of the target grid.

10 A step S5-6 is a step of judging whether or not an undecided grid exists. In a case where the undecided grid exists, the flow returns to the step S5-4, then processing related to the steps S5-4 and S5-5 are executed to a next grid. In the triangle which is targeted in the step S5-3, when the ink quantity is determined for all the grids, the flow advances to a step S5-7. The step S5-7, which is a step of judging whether or not an unprocessed triangle exists, judges whether or not processing is terminated for the plural triangles separated in the step S5-2. In a case where

TOP SECRET

the unprocessed triangle exists, the flow returns to the step S5-3, then processing from the step S5-3 to the step S5-6 are repeated. In a case where processing is terminated for all the triangles of the tetrahedron selected in the step S5-2, the flow advances to a step S5-8. The step S5-8 is a step of judging whether or not an unprocessed tetrahedron exists. In a case where the unprocessed tetrahedron exists, the flow returns to the step S5-2, then processing from the step S5-2 to the step S5-7 are repeated. In a case where processing is terminated for all the tetrahedrons, the flow advances to a step S5-9. The step S5-9 is a step of judging whether or not unprocessed ink color exists. In a case where the unprocessed ink color exists, the flow returns to the step S5-1, then processing from the step S5-1 to the step S5-8 are repeated. In a case where processing is terminated for all the ink colors, the flow advances to a portion 3-2.

Next, concrete processing contents in the step S5-3 of executing the two-dimensional interpolation processing to the target triangle will be explained with reference to Fig. 6 and the following drawings.

Fig. 6 is a view indicating ink contour lines of the internal interpolation result in a case where ink quantity on three sides of a certain triangle are indicated by curves as shown in Fig. 6. In Fig. 6, change of the ink quantity on a side OA is indicated by

REF ID: A42060

a graph which is on the right of the side OA, and a peak of the ink quantity reaches 90%. The change of the ink quantity on a side OB is indicated by a graph which is on the left upper of the side OB, and a peak of the ink quantity reaches 30%. The change of the ink quantity on a side AB is indicated by a graph which is under the side AB, and a peak of the ink quantity reaches 60%.

Figs. 7 and 8 are flow charts for detailedly explaining the two-dimensional interpolation processing executed to the target triangle. Hereinafter, explanations related to Figs. 7 and 8 are described with reference to a case in Fig. 6 as an example.

In Fig. 7, a step S7-1 is a step of detecting the maximum value points of the ink quantity on three sides of the target triangle. A step S7-2 is a step of obtaining magnitude relationship among three maximum values of the three sides. A step S7-3, which is an interpolation step among the maximum value points on the three sides, performs an interpolation operation from values of both ends among the points by connecting the points of the three maximum values on the three sides by straight lines. A step S7-4 is a step of creating an ink contour line by connecting ink quantity same-level points on total six lines consisted of the three sides of the target triangle and three straight lines created according to the three maximum value

FOR NO. 672060

line DJ and a straight line DO are respectively
connected in the step S8-6. In the example shown in
Fig. 6, since the interval s between the contour lines
is expressed by $s = 15$, a contour line for the initial
value $i = 75$ is created as a line G0-G1-G2-G3, and a
5 contour line for the initial value $i = 60$ is created as
a line H0-H-H1-H2. If No in the step S8-4, the flow
advances to the step S8-5. The step S8-5 is a step of
judging whether or not relationship among h , i and j is
10 expressed by an expression of $h > i \geq j$. If Yes in the
step S8-5, points of the value i between a straight
line DA and a straight line AH, between a straight line
HB and a straight line HJ, between the straight line HJ
and a straight line DJ and between the straight line DJ
15 and a straight line DO are respectively connected in
the step S8-7. In the example shown in Fig. 6, contour
lines for the initial value $i = 45$ are created as a
line I0-I1 and a line I2-I3-I4-I5, and contour lines
for the initial value $i = 30$ are created as a line J0-
20 J1 and a line J2-J-J3. If No in the step S8-5, the
flow advances to the step S8-8. The step S8-8 is a
step of respectively connecting points of the value i
between the straight line DA and the straight line AH,
between the straight line HB and a straight line BJ and
25 between the straight line JD and the straight line DO.
In the example shown in Fig. 6, contour lines for the
initial values $i = 15$ are created as a line K0-K1, a

TOP SECRET

line K2-K3 and a line K4-K5. The step S8-9 is a step of judging whether or not the initial value i is expressed by an expression of $i = 0$. If Yes in the step S8-9, creation of the contour lines for all the target triangles is terminated, and the flow advances to a portion 7-2. If No in the step S8-9, the flow advances to the step S8-10. In the step S8-10, an operation of $i = i - s$ is performed. In the step S8-11, it is judged whether or not $i > 0$. If Yes in the step S8-11, the flow returns to the step S8-4. If No in the step S8-11, an operation of $i = 0$ is performed in the step S8-12, and the flow returns to the step S8-4. As explained above, loop processing from the step S8-4 to the step S8-12 are repeated until a contour line value is settled into a state of $i = 0$. In Fig. 6, an example of setting the interval s as $s = 15$ is indicated in order to simplify the explanation. However, in order to make a more precise grid value, it is needless to say that the contour line should be created every one step by setting s as $s = 1$.

Hereinafter, with respect to a case that ink curves of three sides are different from those shown in Fig. 6, its operations will be explained regarding examples shown in Figs. 9, 10 and 11.

Fig. 9 shows an example of a case that the ink quantity maximum values on the three sides are identical each other. In this case, although it is not

FOR THE 20-612000

5
10
15
20

specified in Fig. 8, only the step S8-8 being the step
of creating the contour lines is executed, and contour
lines as shown in Fig. 9 are created. Fig. 10 shows a
case that the ink quantity on one side is equal to zero
5 and the maximum values on other two sides are identical
each other. In this case, points of the value i
between the straight line DA and the straight line AH
and between the straight line HB and the straight line
DO are respectively connected, and contour lines as
10 shown in Fig. 10 are created. Fig. 11 shows a case
that the maximum values on the two sides are identical
each other and points of these maximum values exist on
a point A. In this case, since points D, A and H are
the same point, contour line creating processing is not
15 executed in the step S8-6 shown in Fig. 8. In the step
S8-7, the contour line does not exist because the
points D, A and H are the same point between the
straight line DA and the straight line AH, the contour
line creating processing is not executed because the
20 points D and H are the same point between the straight
line HJ and the straight line DJ, and processing of
respectively connecting the points of the value i is
executed only between the straight line HB and the
straight line HJ and between the straight line DJ and
25 the straight line DO. In the step S8-8, the contour
line does not exist because the points D, A and H are
the same point between the straight line DA and the

TOP SECRET

straight line AH, and processing of respectively
connecting the points of the value i is executed only
between the straight line BJ and a straight line JO and
between the straight line JO and the straight line DO,
5 then contour lines as shown in Fig. 11 are created.

Fig. 12 is a view for explaining an example of
interpolation processing executed inside a triangle
formed by vertexes W-C-Bk shown in Fig. 2, and
indicating examples of curves related to ink color
10 tables of the C, M, Y and K colors on each of sides.
Figs. 13A to 13D show the contour lines every ink color
in Fig. 12. Fig. 13A indicates the contour lines of C
ink and this case corresponds to a case in Fig. 11.
Fig. 13B indicates the contour lines of M ink and this
15 case corresponds to a case in Fig. 10. Fig. 13C
indicates the contour lines of Y ink and this case also
corresponds to the case in Fig. 10. Fig. 13D indicates
the contour lines of K ink and this case corresponds to
the case in Fig. 10, however, since the K ink is
20 injected from halfway, a region of which ink quantity
is zero widely exists and the contour lines of the K
ink are created from halfway.

In this manner, in the present embodiment, the
internal interpolation processing is correspondingly
25 executed every ink color on the basis of ink quantity
curves on three sides of a triangle, then the optimum
and independent ink contour lines are created from the

FOR REFERENCE

ink quantity curves on the three sides. Therefore, by
controlling the ink (k ink) dyeing points on a gray
axis and six hues, i.e., seven ink (k ink) dyeing
points on tables of seven lines W-Bk, C-Bk, M-Bk, Y-Bk,
5 R-Bk, G-Bk and B-Bk, the tables of the ink color
separation table unit 105 can be controlled in an input
color space in a manner that the ink (k ink) dyeing
points can be three dimensionally and sequentially
controlled by total six planes of a triangle WO-RO-MO,
10 a triangle WO-MO-BO, a triangle WO-BO-CO, a triangle
WO-CO-GO, a triangle WO-GO-YO and a triangle WO-YO-RO.
Accordingly, the tables, in which the optimum UCR
quantity or the optimum BG quantity is set every hue,
are created, and the tables, in which influence of
15 graininess caused by the black ink can be possibly
reduced while maximizing the color reproduction region
in the printer, can be set.

In the conventional system, since non-linear
characteristic in case of the mixture of plural color
20 inks can not be sufficiently absorbed, there occurred a
problem that distorted characteristic is appeared in
lightness, hue and chroma. However, according to the
present embodiment, the internal ink quantity can be
smoothly changed by a method of dividing a cube into
25 plural tetrahedrons, separating those tetrahedrons into
plural triangles and connecting points of the same
level value of the ink quantity on the three sides of

20250706120000

each triangle, thereby realizing color reproduction of suppressing the distorted characteristic in the lightness, the hue and the chroma.

In the K ink dyeing UI 1402-1 shown in Fig. 14, since the K ink dyeing points on each line set in the step S3-4 shown in Fig. 3 can be manually instructed, a sensitive adjustment can be performed.

(Second Embodiment)

The second embodiment which is obtained by modifying the first embodiment executes non-linear approximation processing of ink quantity contour lines as in Fig. 16 in a step S7-5 shown in Fig. 15.

According to the second embodiment, a contour line varying rectangularly can be corrected into the contour line which is smoothly and sequentially varied. Accordingly, generation of a pseudo outline in case of extreme changing of the ink quantity can be suppressed.

In the following explanation, the same processing as that in the first embodiment will be omitted to explain, and processing different from that in the first embodiment will be explained.

In case of executing two-dimensional interpolation processing to a target triangle in the step S5-3 shown in Fig. 5, the non-linear approximation processing of the above ink quantity contour lines is executed.

The two-dimensional interpolation processing for the target triangle executed in the second embodiment

FOR THE

will be explained with reference to Fig. 15.

The step S7-1 is a step of detecting maximum value points of the ink quantity on three sides of the target triangle. The step S7-2 is a step of obtaining
5 magnitude relationship among three maximum values of the three sides. The step S7-3, which is an interpolation step among the maximum value points on the three sides, performs an interpolation operation from values of both ends among the points by connecting
10 the points of the three maximum values on the three sides by straight lines. The step S7-4 is a step of creating an ink contour line by connecting ink quantity same-level points on total six lines consisted of the three sides of the target triangle and three straight
15 lines created according to the three maximum value points. A step S15-5, which is a step of executing the non-linear approximation processing of the ink quantity contour lines, non-linearly approximates a portion of rectangularly changing in a region inside the triangle
20 among the ink quantity contour lines created in the step S7-4 such that the ink quantity contour lines are smoothly created.

It should be noted that processing executed in the steps S7-1 to S7-4 are the same as those in the first
25 embodiment.

A detailed explanation of the step S15-5 will be given with reference to Fig. 17.

FIG. 15

5 A step S17-1, which is a step of setting an approximation parameter a , sets the non-linearity degree in case of creating non-linear approximation curves. The approximation parameter a can be set as $a = 1, 2, 3, 4, \dots$. As in Fig. 18, when the parameter a is set as $a = 1$, the approximation degree increases with linear approximation, and when the parameter a is increased as $a = 2, 3, 4, \dots$, the approximation degree decreases while smoothness of the ink quantity contour lines increases. A user can set the approximation parameter a in accordance with characteristic of a printer. Although there are various methods as method of creating the non-linear approximation curves, e.g., in case of using spline curves, creation of the non-linear approximation curves can be attained by setting that when the parameter $a = 1$, a curve is a primary spline curve, when the parameter $a = 2$, a curve is a secondary spline curve, when the parameter $a = 3$, a curve is a tertiary spline curve, and when the parameter $a = 4$, a curve is a quartic spline curve.

25 A step S17-2, which is a step of setting an initial value $i = d - s$, sets the initial value of the ink quantity contour line in case of executing the non-linear approximation processing. A step S17-3 is a step of judging whether or not relationship among d , i and j is expressed by an expression of $d > i > j$. If

FOR 20 6 2060

No in the step S17-3, the flow returns to a portion 5-2 to terminate the non-linear approximation processing of the ink quantity contour lines. If Yes in the step S17-3, the flow advances to a step S17-4.

5 The step S17-4, which is a step of setting vertexes, sets vertexes G0, G1, G2 and G3 structuring a contour line when the initial value i is set as $i = 75$ in an example in Fig. 16. A step S17-5, which is a step of creating the non-linear approximation curves,
10 creates non-linear curves on the basis of a set value of the approximation parameter a and set vertexes. In an example in Fig. 16, for the vertexes G0, G1, G2 and G3 respectively connected by a thin line, the approximation curve represented by a thick line is
15 created. A step S17-6 is a step of performing an operation of $i = i - s$. In the example in Fig. 16, the value of i is set as $i = 60$, thereafter, a loop processing from the step S17-3 to the step S17-6 is repeated.

20 When the value of i is set as $i = 60$, vertexes H, H1 and H2 are selected in the step S17-4 and the non-linear approximation curve is created in the step S17-5. When the value of i is set as $i = 45$, vertexes I2, I3, I4 and I5 are selected in the step S17-4 and the
25 non-linear approximation curve is created in the step S17-5.

When the value of i is set as $i = 30$, a judgment

FOR COPY 672060

result of No is selected in the step S17-3, and the flow returns to a portion 5-2.

Hereinafter, with respect to a case that the ink quantity curves on the three sides are different from those in the example in Fig. 16, operations regarding examples in Figs. 9, 10 and 19 will be explained. Fig. 9 shows an example of a case that the ink quantity maximum values on the three sides are identical each other. In this case, the contour lines as shown in Fig. 11 are created similar to a case of the first embodiment. Fig. 10 shows a case that the ink quantity on one side is equal to zero and the maximum values on other two sides are identical each other. Also, in this case, the contour lines as shown in Fig. 10 are created similar to a case of the first embodiment. Fig. 13 shows a case that the maximum values on the two sides are identical each other and points of these maximum values exist on a point A. In this case, the non-linear approximation processing of the ink contour lines as in the step S15-5 is executed, and contour lines as shown in Fig. 19 are created.

The ink contour lines every ink color are shown in Figs. 20A to 20D.

Fig. 20A indicates the contour lines of the C ink quantity, and this case corresponds to a case in Fig. 19. Fig. 20B indicates the contour lines of the M ink quantity, and this case corresponds to the case in Fig.

FOR COPY

10. Fig. 20C indicates the contour lines of the Y ink quantity, and this case also corresponds to the case in Fig. 10. Fig. 20D indicates the contour lines of the K ink quantity. This case corresponds to the case in Fig. 10, however, since the K ink is injected from halfway, a region of which ink quantity is zero widely exists and the contour lines of the K ink quantity are created from halfway.

(Third Embodiment)

10 In the above embodiments, as ink colors available in a printer, a case of using four colors of C, M, Y and K is indicated. However, a case of such a printer available for total six colors of additionally using light and dark inks for cyan and magenta can be also easily realized by only adding two ink colors. In this case, similar to a case of setting the ink (K ink) dyeing point, a new UI of setting a dark ink dyeing start point is provided for the case in Fig. 21, and dark cyan and dark magenta inks dyeing points can be controlled in a manner that dark ink dyeing points can be three dimensionally and sequentially controlled by total seven points on lines W-Bk, W-C, W-M, W-Y, W-R, W-G and B-Bk.

25 In case of dealing another color ink such as red, green or the like other than the C, M, Y and K colors, intermediate points RM, RY, GY, and GC are newly set on intermediate portions between points R and M, R and Y,

TOP SECRET

G and Y, and G and C. Then, total ten tetrahedrons of W-C-B-Bk, W-B-M-Bk, W-M-RM-Bk, W-RM-R-Bk, W-R-RY-Bk, W-RY-Y-Bk, W-Y-GY-Bk, W-GY-G-Bk, W-G-GC-Bk and W-GC-C-Bk are defined, thereby easily providing the optimum ink color separation in the printer available for six colors even in case of increasing ink colors.

In this manner, in case of using light color ink other than colors of the C, M, Y and K inks, the optimum color separation can be provided.

Similarly, in case of using another color ink such as red, green or the like, the optimum color separation can be provided.

(Fourth Embodiment)

The above embodiments are performed by a controller inside the printer. However, the present invention is not limited to this case, but the present invention can be realized also in case of downloading related data to a LUT in software of a driver inside a computer shown in Fig. 14.

(Fifth Embodiment)

In the above embodiments, as a device for outputting image data to the printer, the computer as shown in Fig. 14 is used. However, the device is not limited to the computer, but the device, which can transmit image data to the printer such as the one capable of temporarily storing image data taken by a digital camera or the like and transmitting the image

TOP SECRET

data to the connected printer, is applicable.

In the above mentioned embodiments, the device for transmitting the image data and the printer exist independently. However, the present invention can be conducted by only the printer itself, in a case where the image data which is input by input means such as the digital camera or the like is stored into any memory medium, and an equipment of capturing the image data in that memory medium is attached to the printer itself.

(Sixth Embodiment)

In the above embodiments, as shown in Fig. 14, as an input device for inputting patch samples, a colorimeter is used. However, the input device is not limited to the colorimeter but may be any device such as a flat-bed scanner, a drum scanner or the like which can capture print data into the computer and check characteristic of inks used in the printer.

(Seventh Embodiment)

In the above embodiments, as an input color space of an ink color separation table for defining a color reproduction region of a color printer, an RGB color space is used. However, the input color space is not limited to the RGB color space but may be any one capable of three dimensionally defining the color reproduction region of the printer according to C, M and Y data or three parameters of a, c and b.

(Other Embodiments)

The present invention includes a case where program codes of software for realizing functions of the above embodiments are supplied to an apparatus
5 connected to various devices or a computer in a system so as to realize the functions of the above embodiments and operate the various devices and then the various devices are to be operated in accordance with programs stored in the computer (or CPU or MPU) in the system or
10 the apparatus.

In this case, the program codes themselves of the software realize the functions of the embodiments, and the program codes themselves and means for supplying the program codes to the computer, e.g., a storage
15 medium storing such the program codes constitute the present invention.

The storage medium for storing the program codes can be, e.g., a floppy disk, a hard disk, an optical disk, a magneto-optical disk, a CD-ROM, a magnetic
20 tape, a non-volatile memory card, a ROM or the like.

It is needless to say that the program codes are included in the embodiments of the present invention not only a case where the functions of the above
embodiments are realized by the execution of the
25 supplied program codes by the computer, but also a case where the program codes realize the functions of the above embodiments cooperating with an OS (operating

TOP SECRET

system) functioning on the computer or another application software.

Further, it is needless to say that the present invention includes a case where the supplied program codes are once stored in a memory provided in a function expansion board inserted in the computer or a function expansion unit connected to the computer, and then a CPU or the like provided in the function expansion board or the function expansion unit executes all the process or a part thereof on the basis of the instructions of the program codes, thereby realizing the functions of the above embodiment.

As above, the present invention has been explained on the basis of the preferable embodiments. However, the present invention is not limited to the above embodiments, but may be modified in various manners within the scope of the following claims.

TOP SECRET